

4110


ASI/310M DA

The 4110 module is an ASI and SMPTE 310M distribution amplifier that handles data rates from 19.39 Mb/s to 270 Mb/s. Use the 4110 for distributing MPEG and ASI signals in your facility. Perfect for use with encoders, servers, and routers.

This module can be monitored locally and remotely. The remote control system is accessed using an Avenue Touch Screen, Avenue PC or your web browser. Modules can be updated with new software as new formats are supported. Software is updated with Avenue's built-in networking capability. Signal status can be monitored via an Avenue Control Panel, and Avenue PC Control Software.

Features

- **Eight outputs**
- **Data rates from 19.39 Mb/s to 270 Mb/s**
- **Use with DVB-ASI**
- **SMPTE 310M signals**
- **Use with encoders, servers and other ASI compliant equipment**
- **Signal presence detection**
- **Local and remote monitoring**



Input Signal

Number	One
Signal Type	DVB-ASI at 270 Mb/s or SMPTE 310M
Impedance	75 Ω
Return Loss	>15 dB DC to 270 MHz
Max Cable Length	300 meters Belden 1694A

Output Signal

Number	Eight
Impedance	75 Ω
Return Loss	>15 dB DC to 270 MHz

General Specifications

Power Consumption	<2.5 watts
Temperature Range	0 to 40°C ambient (all specs met)
Relative Humidity	0 to 95%, noncondensing
Altitude	0 to 10,000 ft
Fusing	1.5 Amp PTC resettable fuse

